

KPC148C

H.R. IR CAMERA



● FEATURES

- (1) Cable management to prevent intentional cable damaging
- (2) High resolution of 520 TV Lines
- (3) High sensitivity in the dark environment, 0.3 Lux / F2.0, 0 Lux (IR ON)
- (4) Day and night features for 24-hour surveillance
- (5) IR distance: up to 35 meters with 35 IR LEDs
- (6) IP67, suitable for outdoor use

● SPECIFICATIONS*

| | |
|----------------------------|--|
| Model | KPC148C |
| Pick up Element | 1/3" HR color CCD image sensor |
| Number of Pixel | 768(H) x 494(V) <NTSC> / 752(H) x 582(V) <PAL> |
| Resolution | 520 TV lines |
| Minimum illumination | 0.3 Lux / F2.0, 0 Lux (IR ON) |
| IR LED | 35 units |
| IR Effective Range | Up to 35 meters |
| S/N Ratio | More than 48dB (AGC off) |
| Electronic Shutter | 1/60 (1/50) to 1/100,000 sec. |
| Lens | f6.0mm / F2.0 |
| Lens Angle | 54° |
| White Balance | ATW |
| AGC | Auto |
| IRIS Mode | AES |
| IP Rating | IP67 |
| Video Output | 1.0Vp-p composite, 75Ω |
| Operating Temperature | 0°C~40°C |
| Power Source (±10%) | DC12V |
| Current Consumption (±10%) | 90mA (IR OFF); 450mA (IR ON) |
| Dimensions (mm)** | 75(Ø) × 142(H) |
| Weight (g) (±5%) | 570 |

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm