

Bullet IR Camera

40 ~ 50 METER VARI-FOCAL BULLET IR CAMERA



CP-TY48VFL4



CP-TY54VFL4



CP-TY55VFL5-E



CP-TY54MVFL5-S

Model	CP-TY48VFL4	CP-TY54VFL4	CP-TY55VFL5-E	CP-TY54MVFL5-S
Image Sensor	1/3Inch Sony HAD CCD			
Effective Pixels	PAL: 500(H) x 582(V) NTSC: 510(H) x 494(V)	PAL: 752(H) x 582(V) ; NTSC: 768(H) x 494(V)		
Lens	4~9mm Vari-Focal			
H-Resolution	480TVL	540TVL	550TVL	540TVL
S/N Ratio	more than 48dB			
Sync System	Internal			
Min. Illumination	0 Lux IR ON			
IR	48 IR LED 40 mtr		78 IR LED 50 mtr	60 IR LED 50 mtr
White Balance	ATW			
C.Video Output	CVBS 1.0Vp-p / 75Ω			
Input Voltage	12V DC			
Operating Temp.	-10°C ~ +50°C			

20 METER HR BULLET IR CAMERA



CP-TY54L2-K



CP-TY54L2

Model	CP-TY54L2-K	CP-TY54L2
Image Sensor	1/3Inch Sony HAD CCD	
Effective Pixels	PAL: 752(H) x 582(V) ; NTSC: 768(H) x 494(V)	
Lens	4mm Fixed Lens	3.6mm Fixed lens
H-Resolution	540TVL	
S/N Ratio	more than 48dB	
Sync System	Internal	
Min. Illumination	0 Lux IR ON	
IR	30 IR LED 20 mtr	
White Balance	ATW	
C.Video Output	CVBS 1.0Vp-p / 75Ω	
Input Voltage	12V DC	
Operating Temp.	-20°C ~ +60°C	-20°C ~ +50°C