DS-7204HVI-S
Standalone DVR

Key Features

- Each channel supports up to 4CIF encoding
- Dual streams
- VGA output
- 1 SATA interface
- Support main and auxiliary video output

Specifications

Video/Audio Input

Video Compression	H.264
Video Input	4 Ch
Video Input Interface	BNC (1.0Vp-p, 75Ω)
Audio Compression	OggVorbis, 16Kbps
Audio Input	1 Ch
Audio Input Interface	RCA (2.0~2.4Vp-p, 1KΩ)
Intercom	1 Ch (Audio Input)

Video/Audio Output

Display	PAL: 704x576 NTSC: 704*480
Recording Resolution	QCIF/CIF/2CIF/DCIF/4CIF
Main Video Output	1 Ch, BNC (1.0Vp-p, 75Ω)
Aux Video Output	1 Ch, BNC (1.0Vp-p, 75Ω)
Recording/Playback	4CIF: 6fps DCIF: 12fps 2CIF: 15fps CIF: 25(P)/30(N)fps
Audio Output	1 Ch, RCA (2.0~2.4Vp-p, 600Ω)
Dual Streams	Yes
Bit Rate	32Kbps ~ 8Mbps
VGA Output	1 (Support 1024x768/60Hz)

Hard Disk Drive

Interface	SATA x 1
Capacity	Each HDD Supports Up to 2000GB

External Interface

Communication Interface	1 RJ45 10M/100M Ethernet Port
RS-485 Port	1 (T+, T-, R+, R-)
USB Interface	1
Alarm Input	4 (Terminal Block)
Alarm Output	1 (Terminal Block)

General

Power Supply	12VDC
Power Consumption	≤40W (w/o HDD or DVD-R/W)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Dimensions	315mm(W)x230mm(D) 45mm(H)
Weight	≤2.8Kg (w/o HDD or DVD-R/W)