

Vandal Proof Dome Camera



Features


- Sony Super HAD II high sensitivity CCD sensor
- 3-Axis Mechanism for free lens rotation
- Option :
Board Lens or Vari-Focal DC Drive Lens
Day & Night (Option: IR-Cut filter Removable, ICR)
Built-in 24 pieces IR-LED




RKY-2Hxx



RKY-2Hxx/1



RYK-2Hxx




RYK-2Hxx/1

Option :



RKY-8719-4
L Type Bracket



Model No.	BL	RYK-2H49	RYK-2H83
	BL & IR	RYK-2H49L	RYK-2H83L
	VF	RYK-2H49VF	RYK-2H83VF
	VF & IR	RYK-2H49LVR3/1	RYK-2H83LVR3/1
Image Device	1/3" Color Sony Super HAD II		1/3" Color Sony Super HAD II
Picture Elements (HxV)	NTSC:510x492, PAL:500x582		NTSC:768x494, PAL:752x582
Resolution	420 TVL		550 TVL
Min. Illumination	0.01 Lux / F1.2 (IR Off) 0 Lux (IR On)		0.02 Lux / F1.2 (IR Off) 0 Lux (IR On)
S/N Ratio	More than 48dB		
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000		
Gamma	0.45		
Iris Control	DC Drive		
Lens Furnished	Vari-Focal Lens (VF) : 3.7~12mm / F1.6~3.0, Wide:76.1°x55.8°, Tele:23.8°x17.9° (HxV) Board Lens (BL) : 3.6mm / F2.0 (option:4.3/6/12mm)		
IR-Cut filter Removable	Available for VR type only		
White Balance	Auto		
Gain Control	High / Low (For VF/VR type only)		
Back Light Comp.	On / Off (For VF/VR type only)		
Sync. System	Internal		
Video Output	1 Vp-p / 75 Ohms		
Infrared Luminary	24 pieces IR-LED (For L type only)		
Wavelength	850 nm		
Illumination Distance	20M max.		
Power Supply	DC12V±10%		
Power Consumption	IR On: 425mA max. IR Off: 117mA max. (35mA increased for VF type)		IR On: 460mA max. IR Off: 155mA max. (35mA increased for VF type)
Operating Temp.	-10°C ~ 50°C		